


SAFE 6 EMERGENCY LIGHTS



SAFE 6 is Teknoware's LED emergency light for areas with 2,5-10 meters high ceilings. The plastic bodied emergency light can be ceiling, wall and flag mounted.

SAFE 6 is splash proof, so the luminaires are suitable for damp locations, for example for parking hall and outdoor roofed shelters.

SAFE 6 emergency light is suitable for open areas. It also works as emergency light for escape routes with a separate lens set.

SELF-CONTAINED EMERGENCY LIGHTS WITH BATTERY AND SELF-TESTING

Product Code	Nominal Supply Voltage	Feature	Backup (h)
TWT0652WM	220-240 V, 50/60 Hz AC	Lumi Test	1
Y0652WM	220-240 V, 50/60 Hz AC	Lumi Test	1

SELF-CONTAINED EMERGENCY LIGHTS WITH BATTERY AND WIRELESS CENTRAL MONITORING

Product Code	Nominal Supply Voltage	Feature	Backup (h)
TWT0652WA	220-240 V, 50/60 Hz AC	Aalto Control, Lumi Test	1
Y0652WA	220-240 V, 50/60 Hz AC	Aalto Control, Lumi Test	1

We reserve the rights to make modifications without notice.
Copyright © 2024 Teknoware. All rights reserved.
Date: May 15, 2024 | Source:
www.teknoware.com/en/emergency-lighting/emergency-lights/emergency-light-product-families/safe-6-emergency-lights



ADDRESSABLE 230 V CENTRALLY SUPPLIED EMERGENCY LIGHTS

Product Code	Nominal Supply Voltage	Feature
TWT0651WK	220-240 V, 50/60 Hz AC, DC	Intelligent Controller, Tapsa Control
Y0651WK	220-240 V, 50/60 Hz AC, DC	Intelligent Controller, Tapsa Control

NON-ADDRESSABLE 230 V CENTRALLY SUPPLIED EMERGENCY LIGHTS

Product Code	Nominal Supply Voltage	Feature	Form
TWT0671W	24-230 V, 50/60 Hz AC, DC		
Y0671W	24-230 V, 50/60 Hz AC, DC		