ESC 10 EMERGENCY EXIT LIGHTS



















The elegant exit light, ESC 10, has an extruded aluminium frame and an edge-lighted light plate.

By utilising a separate support bracket, it can be ceiling, wall or side mounted, or suspended, model TW844, is especially suited for wall installation. ESC 10 can be used in a single or double face configuration. Long-lasting LEDs are used as a light source. The exit symbol is silk screened on the interior side of the light plate.

SELF-CONTAINED ESCAP EMERGENCY EXIT LIGHTS WITH SUPER CAPACITOR AND SELF-TESTING

Product Code	Nominal Supply Voltage	Pictogram	Pictogram Info	Backup (h)
TWS8592WM	220-240 V, 50/60 Hz AC		2-sided, 30 m	1

SELF-CONTAINED ESCAP EMERGENCY EXIT LIGHTS WITH SUPER CAPACITOR AND WIRELESS CENTRAL MONITORING

Product Code	Nominal Supply Voltage	Pictogram	Pictogram Info	Backup (h)
TWS8592WA	220-240 V, 50/60 Hz AC		2-sided, 30 m	1

We reserve the rights to make modifications without notice.

Copyright © 2024 Teknoware. All rights reserved.

Date: May 16, 2024 | Source:

www.teknoware.com/en/emergency-lighting/emergency-exit-lights/emergency-exit-light-pr
oduct-families/esc-10-emergency-exit-lights



BASIC SELF-CONTAINED ESCAP EMERGENCY EXIT LIGHTS WITH SUPER CAPACITOR

Product Code	Nominal Supply Voltage	Pictogram	Pictogram Info	Backup (h)
TWS8592W	220-240 V, 50/60 Hz AC		2-sided, 30 m	1

BASIC SELF-CONTAINED EMERGENCY EXIT LIGHTS WITH BATTERY

Product Code	Nominal Supply Voltage	Pictogram	Pictogram Info	Backup (h)
TW85053W	220-240 V, 50/60 Hz AC		2-sided, 30 m	3
TW80253W	220-240 V, 50/60 Hz AC		2-sided, 40 m	3

ADDRESSABLE 230 V CENTRALLY SUPPLIED EMERGENCY EXIT LIGHTS

Product Code	Nominal Supply Voltage	Pictogram	Pictogram Info
TW80251WK	220-240 V, 50/60 Hz AC, DC		2-sided, 40 m
TW85051WK	220-240 V, 50/60 Hz AC, DC		2-sided, 30 m
TW84451WK	220-240 V, 50/60 Hz AC, DC		2-sided, 30 m

NON-ADDRESSABLE 230 V CENTRALLY SUPPLIED EMERGENCY EXIT LIGHTS

Product Code	Nominal Supply Voltage	Pictogram	Pictogram Info
TW80251W	220-240 V, 50/60 Hz AC, DC		2-sided, 40 m
TW85051W	220-240 V, 50/60 Hz AC, DC		2-sided, 30 m
TW84451W	220-240 V, 50/60 Hz AC, DC		2-sided, 30 m

NON-ADDRESSABLE 24 V CENTRALLY SUPPLIED EMERGENCY EXIT LIGHTS

Product Code	Nominal Supply Voltage	Pictogram	Pictogram Info
TW80241W	24 V, 50/60 Hz AC, DC		2-sided, 40 m
TW85041W	24 V, 50/60 Hz AC, DC		2-sided, 30 m
TW84441W	24 V, 50/60 Hz AC, DC		2-sided, 30 m

