## HEAVY EXIT EMERGENCY EXIT LIGHT TWTA951WK



























## Addressable 230 V centrally supplied emergency exit light

Teknoware Heavy Exit is a robust emergency exit light for demanding conditions such as factories, power plants, machine shops, barns and storage facilities. This nearly maintenance-free luminaire has a heat-tempered glass face and a long-lasting and durable aluminium frame. The Heavy Exit is IP65-rated, so it is highly resistant to dust, water and chemicals, and it will continue to function even in demanding conditions. The colour of the luminaire is gray (RAL 7047).




Product Code	TWTA951WK
Feature	Intelligent Controller, Tapsa Control
Mounting (standard)	wall
Customs Code	94056080
GTIN Code	6438045027197
ETIM Product Class	EC001957
Length	475 mm
Width	235 mm
Height	85 mm
Weight	4 kg
Max Input Power VA	8,3 VA
Max Input Power W	4,6 W
Nominal Supply Voltage	220-240 V, 50/60 Hz AC,DC
Protection Class	1
IP Class	IP65
Temperature Range Min - Max	-30+50 °C
Glow Wire Test of Plastic Materials	650 °C
Viewing Distance	37 m
Light Source	LED
Body Material	aluminium profile
Electrical Installation	3 x 2,5 mm <sup>2</sup>

## ONE OR MORE OF THESE IS ALSO REQUIRED:

## PICTOGRAMS FOR EMERGENCY EXIT LIGHTS



Product Code	Pictogram	Viewing Distance (m)	Compatible Product Groups
PBVA901	<b>5 •</b>	37	Heavy Exit Emergency exit light
PBVA902	₹ →	37	Heavy Exit Emergency exit light





Product Code	Pictogram	Viewing Distance (m)	Compatible Product Groups
PBVA903	← 2	37	Heavy Exit Emergency exit light
PBVA904	<b>公</b>	37	Heavy Exit Emergency exit light



