
SLIMSPOT II: ANGLE















Slimspot II is a recessed emergency light that is effective and seamless. It has an elegant and minimalist appearance, so it blends in with the surroundings and architecture. The broad Slimspot II product family and range of optics offers many options to suit a variety of applications and systems. Slimspot II is designed for indoor lighting, and it has durable metal framing. The standard colour of the luminaire is white. On request, it is also possible to order Slimspot II in black and grey to match the surrounding environment.

The Slimspot II Angle provides an angled light pattern that illuminates fire and safety equipment (such as fire alarm call points, first aid stations, firefighting equipment and panels) vertically with 5 lux according to EN 1838.

for illuminating fire and safety equipment 5 lux according to the requirements of EN 1838

light pattern angle $a = 45^{\circ}$

self-contained or centrally supplied depending on model

IP rating: IP20

installation: recess-mounted material: metal framing

standard colour: white (RAL 9003)

optional colours: black (RAL 9005) and grey (RAL 9006)

SELF-CONTAINED ESCAP EMERGENCY LIGHTS WITH SUPER

CAPACITOR AND SELF-TESTING

Product Code	Nominal Supply Voltage	Feature	Backup (h)	Form
TWSD192WM	220-240 V, 50/60 Hz AC	Escap, Lumi Test	1	



SELF-CONTAINED ESCAP EMERGENCY LIGHTS WITH SUPER CAPACITOR AND WIRELESS CENTRAL MONITORING



Product Code	Nominal Supply Voltage	Feature	Backup (h)
TWSD192WA	220-240 V, 50/60 Hz AC	Aalto Control, Escap, Lumi Test	1

SELF-CONTAINED EMERGENCY LIGHTS WITH BATTERY AND SELF-TESTING

Product Code	Nominal Supply Voltage	Feature	Backup (h)
TWTD152WM	220-240 V, 50/60 Hz AC	Lumi Test	1
TWTD153WM	220-240 V, 50/60 Hz AC	Lumi Test	3

SELF-CONTAINED EMERGENCY LIGHTS WITH BATTERY AND WIRELESS CENTRAL MONITORING

Product Code	Nominal Supply Voltage	Feature	Backup (h)
TWTD152WA	220-240 V, 50/60 Hz AC	Aalto Control, Lumi Test	1
TWTD153WA	220-240 V, 50/60 Hz AC	Aalto Control, Lumi Test	3

ADDRESSABLE 230 V CENTRALLY SUPPLIED EMERGENCY LIGHTS

Product Code	Nominal Supply Voltage	Feature
TWTD151WK	220-240 V, 50/60 Hz AC, DC	Intelligent Controller, Tapsa Control

NON-ADDRESSABLE 230 V CENTRALLY SUPPLIED EMERGENCY LIGHTS

Product Code	Nominal Supply Voltage	Feature	Form
TWTD171W	24-230 V, 50/60 Hz AC, DC		

ADDRESSABLE 24 V CENTRALLY SUPPLIED EMERGENCY LIGHTS

Product Code	Nominal Supply Voltage	Feature	Form
TWTD141WK	24 V, 50/60 Hz AC, DC	Tapsa Control	

