


SOLID: ZONE MIDBAY EMERGENCY LIGHTS



Designed for emergency lighting in open areas, Solid Zone Midbay is an emergency light with an IP65 enclosure.

The luminaire is completely dust proof and water proof, so it is suitable for example for industrial premises, parking halls, as well as for outdoor use. The Solid luminaire uses long-lasting LEDs as its light source.

Special attention has been paid to the design, for easy installation.

SELF-CONTAINED ESCAP EMERGENCY LIGHTS WITH SUPER CAPACITOR AND SELF-TESTING

Product Code	Nominal Supply Voltage	Feature	Backup (h)	Form
TWS3692WM	220-240 V, 50/60 Hz AC	Escap, Lumi Test	1	
Y3692WM	220-240 V, 50/60 Hz AC	Escap, Lumi Test	1	

SELF-CONTAINED ESCAP EMERGENCY LIGHTS WITH SUPER CAPACITOR AND WIRELESS CENTRAL MONITORING

Product Code	Nominal Supply Voltage	Feature	Backup (h)
TWS3692WA	220-240 V, 50/60 Hz AC	Aalto Control, Escap, Lumi Test	1
Y3692WA	220-240 V, 50/60 Hz AC	Aalto Control, Escap, Lumi Test	1

SELF-CONTAINED EMERGENCY LIGHTS WITH BATTERY AND SELF-TESTING

We reserve the rights to make modifications without notice.
Copyright © 2024 Teknoware. All rights reserved.
Date: May 09, 2024 | Source:
www.teknoware.com/en/emergency-lighting/emergency-lights/emergency-light-product-families/solid-zone-midbay-emergency-lights

Teknoware Oy | P.O. Box 19, 15101 Lahti | Ilmarisentie 8, 15200 Lahti Finland
Tel +358 3 883 020 | VAT-number FI01494751 | teknoware.com | emexit@teknoware.com



Product Code	Nominal Supply Voltage	Feature	Backup (h)
TWT3652WM	220-240 V, 50/60 Hz AC	Lumi Test	1
Y3652WM	220-240 V, 50/60 Hz AC	Lumi Test	1
TWT3653WM	220-240 V, 50/60 Hz AC	Lumi Test	3
Y3653WM	220-240 V, 50/60 Hz AC	Lumi Test	3

SELF-CONTAINED EMERGENCY LIGHTS WITH BATTERY AND WIRELESS CENTRAL MONITORING

Product Code	Nominal Supply Voltage	Feature	Backup (h)
TWT3652WA	220-240 V, 50/60 Hz AC	Aalto Control, Lumi Test	1
Y3652WA	220-240 V, 50/60 Hz AC	Aalto Control, Lumi Test	1
TWT3653WA	220-240 V, 50/60 Hz AC	Aalto Control, Lumi Test	3
Y3653WA	220-240 V, 50/60 Hz AC	Aalto Control, Lumi Test	3

ADDRESSABLE 230 V CENTRALLY SUPPLIED EMERGENCY LIGHTS

Product Code	Nominal Supply Voltage	Feature
TWT3751WK	220-240 V, 50/60 Hz AC, DC	Intelligent Controller, Tapsa Control
TWT3651WK	220-240 V, 50/60 Hz AC, DC	Intelligent Controller, Tapsa Control
Y3651WK	220-240 V, 50/60 Hz AC, DC	Intelligent Controller, Tapsa Control

NON-ADDRESSABLE 230 V CENTRALLY SUPPLIED EMERGENCY LIGHTS

Product Code	Nominal Supply Voltage	Feature	Form
TWT3671W	24-230 V, 50/60 Hz AC, DC		
Y3671W	24-230 V, 50/60 Hz AC, DC		

ADDRESSABLE 24 V CENTRALLY SUPPLIED EMERGENCY LIGHTS

Product Code	Nominal Supply Voltage	Feature	Form
TWT3641WK	24 V, 50/60 Hz AC, DC	Tapsa Control	

We reserve the rights to make modifications without notice.

Copyright © 2024 Teknoware. All rights reserved.

Date: May 09, 2024 | Source:

www.teknoware.com/en/emergency-lighting/emergency-lights/emergency-light-product-families/solid-zone-midbay-emergency-lights

Teknoware Oy | P.O. Box 19, 15101 Lahti | Ilmarisentie 8, 15200 Lahti Finland
Tel +358 3 883 020 | VAT-number FI01494751 | teknoware.com | emexit@teknoware.com

