

WEBACM PC SOFTWARE TST5161



WebACM PC Software for addressable Central Battery Units

Product Code	TST5161
Customs Code	85044090
GTIN Code	6438045019536
ETIM Product Class	EC002537

ONE OR MORE OF THESE IS ALSO REQUIRED:

WEBCM CENTRAL MONITORING SYSTEM /
WEBACM CENTRAL MONITORING
SOFTWARE



Product Code	Product Name	Compatible Product Groups
TST6526	WebACM Interface TST6526	TKT65C Central Battery Systems
TST6626	WebACM Interface TST6626	TKT66C Central Battery Systems
TST6726	WebACM Interface TST6726	TKT67C Central Battery Systems
TST6826	WebACM Interface TST6826	TKT68C Central Battery Systems

ADDRESSABLE 230 V CENTRAL BATTERY
SYSTEMS



Product Code	Nominal Supply Voltage	Number of Output Circuits	Max Load of Circuits (VA)
TKT6716C	3~ N/PE 220-240/380-415 VAC, 50/60 Hz	16 x 350 VA / W	
TKT6724C	3~ N/PE 220-240/380-415 VAC, 50/60 Hz	24 x 350 VA / W	
TKT6732C	3~ N/PE 220-240/380-415 VAC, 50/60 Hz	32 x 350 VA / W	
TKT6740C	3~ N/PE 220-240/380-415 VAC, 50/60 Hz	40 x 350 VA / W	
TKT6748C	3~ N/PE 220-240/380-415 VAC, 50/60 Hz	48 x 350 VA / W	
TKT6756C	3~ N/PE 220-240/380-415 VAC, 50/60 Hz	56 x 350 VA / W	
TKT6808C	1~ N/PE 220-240 VAC, 50/60 Hz	8 x 350 VA / W	
TKT6816C	1~ N/PE 220-240 VAC, 50/60 Hz	16 x 350 VA / W	
TKT6824C	1~ N/PE 220-240 VAC, 50/60 Hz	24 x 350 VA / W	

We reserve the rights to make modifications without notice.
Copyright © 2024 Teknoware. All rights reserved.
Date: May 18, 2024 | Source: www.teknoware.fi/en/webacm-pc-software-tst5161

Teknoware Oy | P.O. Box 19, 15101 Lahti | Ilmarisentie 8, 15200 Lahti Finland
Tel +358 3 883 020 | VAT-number FI01494751 | teknoware.com | emexit@teknoware.com



Product Code	Nominal Supply Voltage	Number of Output Circuits	Max Load of Circuits (VA)
TKT6808CF	3~ N/PE 220-240/380-415 VAC, 50/60 Hz	8 x 350 VA / W	
TKT6816CF	3~ N/PE 220-240/380-415 VAC, 50/60 Hz	16 x 350 VA / W	
TKT6824CF	3~ N/PE 220-240/380-415 VAC, 50/60 Hz	24 x 350 VA / W	
TKT6608C	1~ N/PE 220-240 VAC, 50/60 Hz	8 x 350 VA / W	
TKT6616C	1~ N/PE 220-240 VAC, 50/60 Hz	16 x 350 VA / W	
TKT6624C	1~ N/PE 220-240 VAC, 50/60 Hz	24 x 350 VA / W	
TKT6608CF	3~ N/PE 220-240/380-415 VAC, 50/60 Hz	8 x 350 VA / W	
TKT6616CF	3~ N/PE 220-240/380-415 VAC, 50/60 Hz	16 x 350 VA / W	
TKT6624CF	3~ N/PE 220-240/380-415 VAC, 50/60 Hz	24 x 350 VA / W	
TKT6608CFP	3~ N/PE 220-240/380-415 VAC, 50/60 Hz	8 x 350 VA / W	
TKT6616CFP	3~ N/PE 220-240/380-415 VAC, 50/60 Hz	16 x 350 VA / W	
TKT6624CFP	3~ N/PE 220-240/380-415 VAC, 50/60 Hz	24 x 350 VA / W	
TKT6508C	1~ N/PE 220-240 VAC, 50 Hz	8 x 250 VA / W	
TKT6516C	1~ N/PE 220-240 VAC, 50 Hz	16 x 250 VA / W	
TKT6524C	1~ N/PE 220-240 VAC, 50 Hz	24 x 250 VA / W	
TKT6508CP	1~ N/PE 220-240 VAC, 50 Hz	8 x 250 VA / W	
TKT6516CP	1~ N/PE 220-240 VAC, 50 Hz	16 x 250 VA / W	
TKT6524CP	1~ N/PE 220-240 VAC, 50 Hz	24 x 250 VA / W	

