#### SOLID EXIT EMERGENCY EXIT LIGHT TWT3071WE



























# 24-230 V centrally supplied emergency exit light with downlight function

Solid is Teknoware's IP65 class exit and emergency light product family. Solid is designed for demanding conditions. Wall mounted, one sided Solid exit light comes with easily changeable pictograms. Special attention has been paid to the design, for easy installation.

The luminaire is completely dust proof and water proof, so it is suitable for example for industrial premises and parking halls. Escap and centrally supplied luminaires are suitable also for outdoor use.

The range also has a model with a downlight function, which is suitable for example for mounting above a door.



#### INDIVIDUALLY PACKED LIGHTS

Product Code

Y3071WE140

Product Code	TWT3071WE
Mounting (standard)	wall, surface
Customs Code	94056080
GTIN Code	6438045023090
ETIM Product Class	EC001957
Length	371 mm
Width	181 mm
Height	57 mm
Weight	1,35 kg
Max Input Power VA	2 VA (24 V), 4,5 VA (230 V)
Max Input Power W	1,5 W (24 V), 2 W (230 V)
Nominal Supply Voltage	24-230 V, 50/60 Hz AC, DC
Protection Class	III(24V),II(230V)
IP Class	IP65
Temperature Range Min - Max	-30+50 °C
Glow Wire Test of Plastic Materials	650 °C
Viewing Distance	30 m
Light Source	LED
Body Material	plastic
Colour	RAL9003
Electrical Installation	2 x 2,5 mm² (24 V), 3 x 2,5 mm² (230 V)
Luminous Flux	48 lm

We reserve the rights to make modifications without notice.

Copyright © 2024 Teknoware. All rights reserved.


Date: May 03, 2024 | Source:

www.teknoware.fi/en/emergency-lighting-1/solid-exit-emergency-exit-light-twt3071we



### Downlight chart for Exit Lights

Tables of 1 lux and 0,5 lux, under the Exit Light. Level of measurement 0,02 m, measurement result with battery operation.



TWT3071WE


Mounting height (m)	Below the light lux	R1 (m)	R4 (m)	R1 (m)	R4 (m)
		1 lux	1 lux	0,5 lux	0,5 lux
2	17	1,5	1,5	2	2
2,5	12	2	2	2,5	2,5
3	7,5	2	2	2,5	2,5
4	4	2	2	2,5	2,5
5	2,5	2	2	2,5	2,5
6	1,5	1,5	1,5	2,5	2,5

### ONE OR MORE OF THESE IS ALSO REQUIRED:

# PICTOGRAMS FOR EMERGENCY EXIT LIGHTS



Product Code	Pictogram	Viewing Distance (m)	Compatible Product Groups
PB3001E	← ½	30	Solid Exit Emergency Exit Lights
PB3002E	<b>₹</b> →	30	Solid Exit Emergency Exit Lights
PB3003E	<b>₽</b>	30	Solid Exit Emergency Exit Lights





Product Code	Pictogram	Viewing Distance (m)	Compatible Product Groups
PB3005E	<b>公</b>	30	Solid Exit Emergency Exit Lights

### **OPTIONAL ACCESSORIES:**

# OPTIONAL MOUNTING ACCESSORIES FOR EMERGENCY EXIT LIGHTS



Product Code	Product Name	Compatible Product Groups
TWT3001	Solid Recess Mounting Frame TWT3001	Solid Exit Emergency Exit Lights, Solid Exit 2 Emergency Exit Lights, Solid: Line Lowbay Emergency Lights, Solid: Line Midbay Emergency Lights, Solid: Zone Lowbay Emergency Lights
TWT3002	Solid Wall bracket TWT3002	Solid Exit Emergency Exit Lights, Solid Exit 2 Emergency Exit Lights, Solid: Line Lowbay Emergency Lights, Solid: Line Midbay Emergency Lights, Solid: Zone Lowbay Emergency Lights
TWT3003	Solid Flag bracket TWT3003	Solid Exit Emergency Exit Lights, Solid Exit 2 Emergency Exit Lights, Solid: Line Lowbay Emergency Lights, Solid: Line Midbay Emergency Lights, Solid: Zone Lowbay Emergency Lights, Solid: Zone Midbay Emergency Lights
TWT3004	Solid Ceiling bracket TWT3004	Solid Exit Emergency Exit Lights, Solid Exit 2 Emergency Exit Lights, Solid: Line Lowbay Emergency Lights, Solid: Line Midbay Emergency Lights, Solid: Zone Lowbay Emergency Lights, Solid: Zone Midbay Emergency Lights



