

STEEL EMERGENCY EXIT LIGHT TWTE251WK



220-240 V
50/60 Hz
AC, DC

LED

IP
20

26 m

650 °C

-O-

TC

IC

CE

EN
1838

EN
60598-2-22



Addressable 230 V centrally supplied emergency exit light

Teknoware Steel is an elegant emergency exit light for high-class premises. The light plate in the elegant luminaire has a narrow, glossy metal frame. The luminaire can be used as one or two sided, and depending on the model, it is suitable for ceiling, wall, suspension or flag mounting.

We reserve the rights to make modifications without notice.

Copyright © 2024 Teknoware. All rights reserved.

Date: May 03, 2024 | Source: www.teknoware.fi/en/steel-emergency-exit-light-twte251wk

Teknoware Oy | P.O. Box 19, 15101 Lahti | Ilmarisentie 8, 15200 Lahti Finland
Tel +358 3 883 020 | VAT-number FI01494751 | teknoware.com | emexit@teknoware.com

 **TEKNOWARE®**

Product Code	TWTE251WK
Feature	Intelligent Controller, Tapsa Control
Mounting (standard)	wall, surface
Customs Code	94056080
GTIN Code	06438045028279
ETIM Product Class	EC001957
Length	291 mm
Width	61 mm
Height	204 mm
Weight	1.4 kg
Max Input Power VA	9,1 VA
Max Input Power W	5,1 W
Nominal Supply Voltage	220-240 V, 50/60 Hz AC, DC
Protection Class	I
IP Class	IP20
Temperature Range Min - Max	-30...+50 °C
Glow Wire Test of Plastic Materials	650 °C
Viewing Distance	26 m
Light Source	LED
Body Material	stainless steel plate
Electrical Installation	3 x 2,5 mm ²

ONE OR MORE OF THESE IS ALSO REQUIRED:

PICTOGRAMS FOR EMERGENCY EXIT LIGHTS




Product Code	Pictogram	Viewing Distance (m)	Compatible Product Groups
PBVEX261E		26	Steel emergency exit light
PBVEX261E1		26	Steel emergency exit light

We reserve the rights to make modifications without notice.
 Copyright © 2024 Teknoware. All rights reserved.
 Date: May 03, 2024 | Source: www.teknoware.fi/en/steel-emergency-exit-light-twte251wk

Teknoware Oy | P.O. Box 19, 15101 Lahti | Ilmarisentie 8, 15200 Lahti Finland
 Tel +358 3 883 020 | VAT-number FI01494751 | teknoware.com | emexit@teknoware.com



Product Code	Pictogram	Viewing Distance (m)	Compatible Product Groups
PBVEX261E2		26	Steel emergency exit light
PBVEX262E	 	26	Steel emergency exit light
PBVEX262E3		26	Steel emergency exit light
PBVEX265E	 	26	Steel emergency exit light
PBVEX265E3		26	Steel emergency exit light



We reserve the rights to make modifications without notice.

Date: May 03, 2024 | Source: www.teknoware.fi/en/steel-emergency-exit-light-twte251wk

Teknoware Oy | P.O. Box 19, 15101 Lahti | Ilmarisentie 8, 15200 Lahti Finland

Tel +358 3 883 020 | VAT-number FI01494751 | teknoware.com | emexit@teknoware.com

