


TRAIL: LINE LOWBAY



Teknoware Trail is an elegant emergency light that is easy to install on a lighting track. Thanks to its unique design, it is suitable for direct mounting on common lighting track systems. The luminaire can also be mounted directly on the ceiling. Trail has a modern and streamlined appearance so it blends in with the surroundings and architecture. Trail’s wide product family and range of optics offer many options to suit a variety of applications and systems.

Trail Line Lowbay is particularly suitable for low spaces. The luminaire provides a long and narrow pattern that illuminates the escape routes efficiently.

- for escape routes
 - self-contained or centrally supplied depending on model
 - installation: surface mounting on a lighting track (compatible with Global Trac and lighting trunking systems) or ceiling mounted
 - material: metal casing
 - colour: white (RAL 9003), other RAL-colours on request
- SELF-CONTAINED ESCAP EMERGENCY LIGHTS WITH SUPER CAPACITOR AND SELF-TESTING

| Product Code | Nominal Supply Voltage | Feature | Backup (h) | Form |
|--------------|------------------------|------------------|------------|------|
| TWSC192WM | 220-240 V, 50/60 Hz AC | Escap, Lumi Test | 1 | |

SELF-CONTAINED ESCAP EMERGENCY LIGHTS WITH SUPER CAPACITOR AND WIRELESS CENTRAL MONITORING

| Product Code | Nominal Supply Voltage | Feature | Backup (h) |
|--------------|------------------------|---------------------------------|------------|
| TWSC192WA | 220-240 V, 50/60 Hz AC | Aalto Control, Escap, Lumi Test | 1 |

We reserve the rights to make modifications without notice.
Copyright © 2024 Teknoware. All rights reserved.
Date: May 02, 2024 | Source:
www.teknoware.fi/en/emergency-lighting/emergency-lights/emergency-light-product-families/trail-line-lowbay



SELF-CONTAINED EMERGENCY LIGHTS WITH BATTERY AND SELF-TESTING

| Product Code | Nominal Supply Voltage | Feature | Backup (h) |
|--------------|------------------------|-----------|------------|
| TWTC152WM | 220-240 V, 50/60 Hz AC | Lumi Test | 1 |
| TWTC153WM | 220-240 V, 50/60 Hz AC | Lumi Test | 3 |

SELF-CONTAINED EMERGENCY LIGHTS WITH BATTERY AND WIRELESS CENTRAL MONITORING

| Product Code | Nominal Supply Voltage | Feature | Backup (h) |
|--------------|------------------------|--------------------------|------------|
| TWTC152WA | 220-240 V, 50/60 Hz AC | Aalto Control, Lumi Test | 1 |
| TWTC153WA | 220-240 V, 50/60 Hz AC | Aalto Control, Lumi Test | 3 |

ADDRESSABLE 230 V CENTRALLY SUPPLIED EMERGENCY LIGHTS

| Product Code | Nominal Supply Voltage | Feature |
|--------------|----------------------------|---------------------------------------|
| TWTC151WK | 220-240 V, 50/60 Hz AC, DC | Intelligent Controller, Tapsa Control |

NON-ADDRESSABLE 230 V CENTRALLY SUPPLIED EMERGENCY LIGHTS

| Product Code | Nominal Supply Voltage | Feature | Form |
|--------------|---------------------------|---------|------|
| TWTC171W | 24-230 V, 50/60 Hz AC, DC | | |

We reserve the rights to make modifications without notice.

Copyright © 2024 Teknoware. All rights reserved.

Date: May 02, 2024 | Source:

www.teknoware.fi/en/emergency-lighting/emergency-lights/emergency-light-product-families/trail-line-lowbay



Teknoware Oy | P.O. Box 19, 15101 Lahti | Ilmarisentie 8, 15200 Lahti Finland

Tel +358 3 883 020 | VAT-number FI01494751 | teknoware.com | emexit@teknoware.com