TRAIL: ZONE MIDBAY













Teknoware Trail is an elegant emergency light that is easy to install on a lighting track. Thanks to its unique design, it is suitable for direct mounting on common lighting track systems. The luminaire can also be mounted directly on the ceiling. Trail has a modern and streamlined appearance so it blends in with the surroundings and architecture. Trail's wide product family and range of optics offer many options to suit a variety of applications and systems.

Trail Zone Midbay provides a broad, even pattern that illuminates open areas efficiently.

for open areas

self-contained or centrally supplied depending on model

installation: surface mounting on a lighting track (compatible with Global Trac and lighting

trunking systems) or ceiling mounted

material: metal casing

colour: white (RAL 9003), other RAL-colours on request

SELF-CONTAINED ESCAP EMERGENCY LIGHTS WITH SUPER

CAPACITOR AND SELF-TESTING

| Product Code | Nominal Supply Voltage | Feature | Backup (h) | Form |
|--------------|------------------------|------------------|------------|------|
| TWSC592WM | 220-240 V, 50/60 Hz AC | Escap, Lumi Test | 1 | |
| TWSC592WMC | 220-240 V, 50/60 Hz AC | Escap, Lumi Test | 1 | |

SELF-CONTAINED ESCAP EMERGENCY LIGHTS WITH SUPER CAPACITOR AND WIRELESS CENTRAL MONITORING





| Product Code | Nominal Supply Voltage | Feature | Backup (h) |
|--------------|------------------------|---------------------------------|------------|
| TWSC592WA | 220-240 V, 50/60 Hz AC | Aalto Control, Escap, Lumi Test | 1 |
| TWSC592WAC | 220-240 V, 50/60 Hz AC | Aalto Control, Escap, Lumi Test | 1 |

SELF-CONTAINED EMERGENCY LIGHTS WITH BATTERY AND SELF-TESTING

| Product Code | Nominal Supply Voltage | Feature | Backup (h) |
|--------------|------------------------|-----------|------------|
| TWTC552WM | 220-240 V, 50/60 Hz AC | Lumi Test | 1 |
| TWTC553WM | 220-240 V, 50/60 Hz AC | Lumi Test | 3 |

SELF-CONTAINED EMERGENCY LIGHTS WITH BATTERY AND WIRELESS CENTRAL MONITORING

| Product Code | Nominal Supply Voltage | Feature | Backup (h) |
|--------------|------------------------|--------------------------|------------|
| TWTC552WA | 220-240 V, 50/60 Hz AC | Aalto Control, Lumi Test | 1 |
| TWTC553WA | 220-240 V, 50/60 Hz AC | Aalto Control, Lumi Test | 3 |

ADDRESSABLE 230 V CENTRALLY SUPPLIED EMERGENCY LIGHTS

| Product Code | Nominal Supply Voltage | Feature |
|--------------|----------------------------|---------------------------------------|
| TWTC551WK | 220-240 V, 50/60 Hz AC, DC | Intelligent Controller, Tapsa Control |

NON-ADDRESSABLE 230 V CENTRALLY SUPPLIED EMERGENCY LIGHTS

| Product Code | Nominal Supply Voltage | Feature | Form |
|--------------|---------------------------|---------|------|
| TWTC571W | 24-230 V, 50/60 Hz AC, DC | | |

