


# SAFE 82 EMERGENCY LIGHTS



SAFE 82 is a high ceiling area LED emergency light, with ceiling and wall mounting as standard. SAFE 82 can be installed at a height of 4-20 meters.

SAFE 82 is particularly easy and quick to install thanks to a separate mounting plate.

SAFE 82 family of luminaires are splash water proof and suitable for damp areas and, for example, parking halls and outdoor roofed shelters.

## ADDRESSABLE 230 V CENTRALLY SUPPLIED EMERGENCY LIGHTS

Product Code	Nominal Supply Voltage	Feature
TWT8251WKH	220-240 V, 50/60 Hz AC, DC	Tapsa Control
Y8251WKH	220-240 V, 50/60 Hz AC, DC	Tapsa Control

## NON-ADDRESSABLE 230 V CENTRALLY SUPPLIED EMERGENCY LIGHTS

Product Code	Nominal Supply Voltage	Feature	Form
TWT8251WH	220-240 V, 50/60 Hz AC, DC		
Y8251WH	220-240 V, 50/60 Hz AC, DC		

We reserve the rights to make modifications without notice.  
Copyright © 2024 Teknoware. All rights reserved.  
Date: May 04, 2024 | Source:  
[www.teknoware.fi/en/emergency-lighting/emergency-lights/emergency-light-product-families/safe-82-emergency-lights](http://www.teknoware.fi/en/emergency-lighting/emergency-lights/emergency-light-product-families/safe-82-emergency-lights)



Teknoware Oy | P.O. Box 19, 15101 Lahti | Ilmarisentie 8, 15200 Lahti Finland  
Tel +358 3 883 020 | VAT-number FI01494751 | [teknoware.com](http://teknoware.com) | [emexit@teknoware.com](mailto:emexit@teknoware.com)