




TKT65C CENTRAL BATTERY SYSTEMS



Central battery system in TKT65xxCX series, as all our Tapsa Control central battery systems, takes care of the testing automatically.

Suitable for medium sized and large buildings.

Technical data:

input voltage 230 VAC

output voltage under normal conditions 230 VAC

output voltage in battery mode 216 VDC

We reserve the rights to make modifications without notice.

Copyright © 2024 Teknoware. All rights reserved.

Date: April 27, 2024 | Source:

www.teknoware.fi/en/emergency-lighting/central-battery-systems/central-battery-systems-product-families/tkt65c-central-battery-systems



battery voltage of 216 V is generated by 18 pieces of 12 V batteries connected in series
8, 16 or 24 output circuits
max 16 luminaires per circuit
ADDRESSABLE 230 V CENTRAL BATTERY SYSTEMS

Product Code	Nominal Supply Voltage	Number of Output Circuits	Max Load of Circuits (VA)
TKT6508C	1~ N/PE 220-240 VAC, 50 Hz	8 x 250 VA / W	
TKT6516C	1~ N/PE 220-240 VAC, 50 Hz	16 x 250 VA / W	
TKT6524C	1~ N/PE 220-240 VAC, 50 Hz	24 x 250 VA / W	
TKT6508CP	1~ N/PE 220-240 VAC, 50 Hz	8 x 250 VA / W	
TKT6516CP	1~ N/PE 220-240 VAC, 50 Hz	16 x 250 VA / W	
TKT6524CP	1~ N/PE 220-240 VAC, 50 Hz	24 x 250 VA / W	