



TKT66C CENTRAL BATTERY SYSTEMS



We recommend TKT66 series in particular for medium sized and large buildings. TKT66 is also a good choice with a central battery system in several independent areas.

TKT66 series central battery system offers an effective solution to supply medium to high number of luminaires. TKT66 series has the advantage of easy and quick installation, as the connectors are conveniently located on the top edge and the

We reserve the rights to make modifications without notice.

Copyright © 2024 Teknoware. All rights reserved.

Date: April 26, 2024 | Source:

www.teknoware.fi/en/emergency-lighting/central-battery-systems/central-battery-systems-product-families/tkt66c-central-battery-systems



Teknoware Oy | P.O. Box 19, 15101 Lahti | Ilmarisentie 8, 15200 Lahti Finland
Tel +358 3 883 020 | VAT-number FI01494751 | teknoware.com | emexit@teknoware.com

output fuses on the connectors.

Technical data:

input voltage 220-240 VAC

output voltage in normal mode 220-240 VAC

output voltage in battery mode 216 VDC

battery voltage of 216 V is generated by 18 pieces of 12 V batteries connected in series

8, 16 or 24 output circuits

8 x 350 VA, 4 x 700 VA or 2 x 1400 VA parallel connections are possible

max 32 luminaires per circuit (please note local restrictions)

ADDRESSABLE 230 V CENTRAL BATTERY SYSTEMS

Product Code	Nominal Supply Voltage	Number of Output Circuits	Max Load of Circuits (VA)
TKT6608C	1~ N/PE 220-240 VAC, 50/60 Hz	8 x 350 VA / W	
TKT6616C	1~ N/PE 220-240 VAC, 50/60 Hz	16 x 350 VA / W	
TKT6624C	1~ N/PE 220-240 VAC, 50/60 Hz	24 x 350 VA / W	
TKT6608CP	1~ N/PE 220-240 VAC, 50/60 Hz	8 x 350 VA / W	
TKT6616CP	1~ N/PE 220-240 VAC, 50/60 Hz	16 x 350 VA / W	
TKT6624CP	1~ N/PE 220-240 VAC, 50/60 Hz	24 x 350 VA / W	
TKT6608CF	3~ N/PE 220-240/380-415 VAC, 50/60 Hz	8 x 350 VA / W	
TKT6616CF	3~ N/PE 220-240/380-415 VAC, 50/60 Hz	16 x 350 VA / W	
TKT6624CF	3~ N/PE 220-240/380-415 VAC, 50/60 Hz	24 x 350 VA / W	
TKT6608CFP	3~ N/PE 220-240/380-415 VAC, 50/60 Hz	8 x 350 VA / W	
TKT6616CFP	3~ N/PE 220-240/380-415 VAC, 50/60 Hz	16 x 350 VA / W	
TKT6624CFP	3~ N/PE 220-240/380-415 VAC, 50/60 Hz	24 x 350 VA / W	

We reserve the rights to make modifications without notice.

Copyright © 2024 Teknoware. All rights reserved.

Date: April 26, 2024 | Source:

www.teknoware.fi/en/emergency-lighting/central-battery-systems/central-battery-systems-product-families/tkt66c-central-battery-systems



Teknoware Oy | P.O. Box 19, 15101 Lahti | Ilmarisentie 8, 15200 Lahti Finland
Tel +358 3 883 020 | VAT-number FI01494751 | teknoware.com | emexit@teknoware.com